



# SINGLE-ROW ANGULAR CONTACT BALL BEARINGS





[www.tldbm-industry.com](http://www.tldbm-industry.com) The items dont list in the form, can be manufactured according to customers' design

Bearing NO. (New)	Bearing NO. (Old)	Basic Size					Role Point	Capacity		Limiting Speed		Weight Kg
		d	D	B	r <sub>12min</sub>	r <sub>34min</sub>	a	Cr	Cor	Grease	Oil	
		mm					mm	kN		r/min		
7020AC	46120J	100	150	24	1.5	0.6	41.2	59	77	4500	6000	1.25
7220CM	36220	100	180	34	2.1	1.1	35.8	120	136	5600	8000	3.71
7220ACM	46220	100	180	34	2.1	1.1	49.6	114	130	4000	5300	3.74
7220BM	66220	100	180	34	2.1	1.1	75.7	100	114	2800	3800	4
7220AC	46220J	100	180	34	2.1	1.1	49.6	114	130	4000	5300	3.25
7320ACM	46320	100	215	47	3	1.1	60.2	164	199	2800	3800	9.61
7320BM	66320	100	215	47	3	1.1	89.6	146	177	2400	3400	8.41
7320B	66320K	100	215	47	3	1.1	89.6	146	177	1900	2700	7.29
7320BT	66320J	100	215	47	3	1.1	89.6	146	177	1900	2700	7.58
7321BM	66321	105	225	49	3	1.1	93.7	155	193	2400	3200	9.51
7022ACJ	46122K	110	170	28	2	1	46.6	76	101	3200	4200	1.9
B7022AC	6022M/YB5	110	170	28	2	1	47	76	101	3200	4200	2.03
7022ACM	46122	110	170	28	2	1	46.7	76	101	4000	5300	2.41
7022AC	46122J	110	170	28	2	1	46.7	76	101	4000	5300	2.16
46722K*		110	175	30	1.1	0.7	49.7	79	104	3200	4200	2.38
7222CM	36222	110	200	38	2.1	1.1	39.8	142	171	5000	7100	5.03
7222CJ	36222K	110	200	38	2.1	1.1	39.8	142	171	4000	5700	4.14
7222C	36222J	110	200	38	2.1	1.1	39.8	142	171	5000	7100	4.07
7222ACM	46222	110	200	38	2.1	1.1	55.1	135	164	3600	4800	4.81
7222AC	46222J	110	200	38	2.1	1.1	55.1	135	164	3600	4800	4.07
7222ACJ	46222K	110	200	38	2.1	1.1	55.1	135	164	2900	3800	4.14
7222BM	66222	110	200	38	2.1	1.1	84	118	144	2600	3400	3.95
7322ACM	46322	110	240	50	3	1.1	65.8	184	231	2600	3400	9.97
7322BM	66322	110	240	50	3	1.1	99.3	164	212	2200	3000	11.5
7322B	66322K	110	240	50	3	1.1	99.3	164	212	1800	2400	9.84
B7322BQ1	166322Q	110	240	50	3	1.1	99.2	164	212	1800	2400	11.4
7024ACM	46124	120	180	28	2	1	49	77	107	3600	5000	2.62
7024AC	46124J	120	180	28	2	1	49	77	107	3600	5000	2.31
7224ACM	46224	120	215	40	2.1	1.1	59.1	146	184	3200	4500	6.04
B7224ACQ1(HAS0(146224QT))	146224QT	120	215	40	2.1	1.1	59	204	239	2600	3600	6.45
7324B	66324	120	260	55	3	1.1	107.2	193	262	1600	2200	14.6
B7324CM	136324	120	260	55	3	1.1	52.9	214	288	3400	4000	14.2
B7324ACM	146324	120	260	55	3	1.1	71.8	206	277	1800	2400	14.2
B7324ACQ1(146324Q)	146324Q	120	260	55	3	1.1	71.8	206	277	1800	2400	14
7324AC	46324J	120	260	55	3	1.1	71.8	204	269	2200	3000	13.7
7026C	36126J	130	200	33	2	1	38.6	99	137	5400	6500	3.33
7226CM	36226	130	230	40	3	1.1	44.1	159	209	4400	5200	7.28
7226ACM	46226	130	230	40	3	1.1	62	151	200	2400	3200	7.26
7226ACJ	46226K	130	230	40	3	1.1	62	151	200	1900	2600	6.23
7226BM	66226	130	230	40	3	1.1	95.5	131	175	2200	3000	7.56
7326B	66326F	130	280	58	4	1.5	115.1	192	268	1800	2400	17.9
7028AC	46128J	140	210	33	2	1	57.3	96	137	3200	4300	3.46
7028ACM	46128	140	210	33	2	1	57.3	96	137	3200	4300	4.14
7228CM	36228	140	250	42	3	1.1	47.1	177	248	4200	5000	8.83
7228ACM	46228	140	250	42	3	1.1	66.5	169	237	2200	3000	8.71
B7228ACYQ1	146228Q	140	250	42	3	1.1	68.5	167	235	2200	3000	8.7
7228BM	66228	140	250	42	3	1.1	102.9	147	207	2000	2800	8.59
7328B	66328	140	300	62	4	1.5	123.2	212	308	1600	2200	21.2
7030ACM	46130	150	225	35	2.1	1.1	61.2	118	170	2400	3000	4.8
7230AC	46230	150	270	45	3	1.1	71.5	186	268	2000	2800	12.1
B7230AC	146230	150	270	45	3	1.1	71.4	174	254	1600	2200	10.6
7330AC	46330	150	320	65	4	1.5	87.6	276	429	1800	2400	25.8
7330B	66330F	150	320	65	4	1.5	87.3	276	428	2300	2000	26.2
I-6014		152	203	25.4	2.1	0.6	31.5	73	118	2300	2000	2.56
B7032ACQ1		160	240	38	2.1	1.1	65.6	124	183	1800	2200	5.74



# SINGLE-ROW ANGULAR CONTACT BALL BEARINGS



[www.tldbm-industry.com](http://www.tldbm-industry.com) The items dont list in the form, can be manufactured according to customers' design.

Bearing NO. (New)	Bearing NO. (Old)	Basic Size					Role Point	Capacity		Limiting Speed		Weight Kg
		d	D	B	r <sub>12min</sub>	r <sub>34min</sub>	a	Cr	Cor	Grease	Oil	
		mm					mm	kN		r/min		
B7032ACM	146132	160	240	38	2.1	1.1	65.6	124	183	1800	2200	5.81
7032ACM	46132	160	240	38	2.1	1.1	65.6	124	183	1800	2200	5.95
7232C	36232	160	290	48	3	1.1	54.1	202	304	2900	3600	14.5
7232AC	46232	160	290	48	3	1.1	76.5	192	289	1900	2600	14.5
7332B	66332F	160	340	68	4	1.5	138.9	259	409	1200	1600	30.8
7034ACQ1	46134Q	170	260	42	2.1	1.1	71.1	153	227	2000	2600	8.27
7034AC	46134	170	260	42	2.1	1.1	71.1	153	227	2000	2600	7.98
7234C	36234	170	310	52	4	1.5	58.2	247	389	2800	3400	17.2
7234AC	46234	170	310	52	4	1.5	82	235	371	1800	2400	17.2
B7234AC	146234	170	310	52	4	1.5	82	217	343	1500	1900	17.4
7236C	36236	180	320	52	4	1.5	59.5	256	418	2700	3200	17.9
7236AC	46236	180	320	52	4	1.5	84.3	244	399	1700	2200	17.9
7336B	66336	180	380	75	4	1.5	155	311	536	1300	1800	37
7038AC	46138	190	290	46	2.1	1.1	79	165	263	1800	2400	10.7
7040AC	46140	200	310	51	2.1	1.1	85	203	331	1700	2200	14.9
7040ACN1		200	310	51	2.1	1.1	85	203	331	1700	2200	14.8
7240C	36240	200	360	58	4	1.5	66.5	279	487	2500	3000	25.2
7240AC	46240	200	360	58	4	1.5	94.3	265	462	1500	2000	25.2
7240B	66240	200	360	58	4	1.5	146.5	238	417	1300	1800	25.8
7244AC	46244	220	400	65	4	1.5	104.7	326	605	1100	1600	36.1
72948AC	2046948	240	320	48	2.1	1.1	89.3	142	250	1000	1500	10
7248B	66248	240	440	72	4	1.5	178.5	322	626	1000	1500	50.9
71952AC		260	360	46	2.1	1.1	95.3	200	380	900	1400	13.8
71956AC		280	380	46	2.1	1.1	99.9	206	405	800	1300	15.7
B71957Y		285	380	46	2.1	1.1	119	188	366	800	1200	14.7
7072CF3	36172	360	540	82	5	1.4	101.3	409	965	600	1000	65.3
71976B		380	520	65	4	1.5	221.4	273	630	500	800	42.1